



Tuxton Heavy Duty Motor Oils Single Grade

Description

Tuxton Heavy Duty Motor Oils (Single-grade) are premium heavy duty crankcase lubricants designed for heavy duty service in construction equipment as well as commercial trucks among others. Tuxton Heavy Duty Motor Oils are engineered with premium quality base oils and the latest additive technology and are available in four different viscosity grades; SAE 10W, SAE 30, SAE 40 and SAE 50.

Performance Features

- Reduced oil consumption
- Excellent deposit control for cleaner engines
- Excellent TBN retention to prevent corrosive wear
- Low ash to minimize deposits
- Excellent shear stability
- Excellent wear protection
- Superior high temperature stability and performance

Applications

- SAE 10: CF
- SAE 30: CF-2,CF
- SAE 40: CF-2,CF
- SAE 50: CF-2,CF
- SAE 10 and 30: Allison C-4
- SAE 30 and 40: US CID A-A-52306

Properties

	10	30	40	50
Viscosity cSt @ 40°C	38.9	104.4	144	189
Viscosity cSt @ 100°C	6.6	12	14.9	17.5
Viscosity Index	124	104	103	100
Flash Point, °F	434	474	472	478
Pour Point, °C	-32	-10	-12	-12
Specific Gravity	0.881	0.8938	0.9	0.8956
TBN	8.25	8.25	8.25	8.25
Sulfated Ash	1.1	1.1	1.1	1.1
API	CF	CF-2/CF	CF-2/CF	CF-2/CF